

MIMO 2 LED BASIC

LED GO!



220-240 V
50-60 Hz

LED



IP66 IK06

TECHNICAL PARAMETERS

Ingress protection:	IP66;
Impact resistance:	IK06;
Nominal power [W]:	27.00; 33.00; 13.00;
Luminous flux [lm]*:	3600; 4550; 1650;
Colour temperature [K]:	4000;
Colour rendering index:	>80;
SDCM:	≤ 5;
Energy efficiency class:	A+;
Material of the body:	PC;
Diffuser type:	MAT;
Mounting version:	surface, suspended;
Dimensions [mm]:	1230/45/50; 1510/45/50; 670/45/50;

*Tolerance +/- 10%

CHARACTERISTICS

MIMO 2 LED BASIC represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED GO! panels offering the best lighting level required and energy savings. The multilayer shade has been made of UV-resistant polycarbonate.

APPLICATION

The multifunctional LED luminaire is designed for use in areas with increased dust and humidity. It is particularly suitable for industrial conditions, car parks (underground and multi-storey ones), sports stadiums, warehouses, transport terminals and underground passages. The luminaire is used both in new applications, as well as in replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended installation using standard equipment.

MIMO 2 LED BASIC

LED GO!

AVAILABLE TYPES

Click >> index, to see details

MIMO 2 LED BASIC 1230/45/50mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions [mm]	Energy efficiency class	Index
27	4000	3600	MAT	1230/45/50	A+	>> 100840

MIMO 2 LED BASIC 1510/45/50mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions [mm]	Energy efficiency class	Index
33	4000	4550	MAT	1510/45/50	A+	>> 100857

MIMO 2 LED BASIC 670/45/50mm

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions [mm]	Energy efficiency class	Index
13	4000	1650	MAT	670/45/50	A+	>> 100765

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2019-10-17



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



68/2019