

SMART LED EVO ASYMMETRIC

LED GO!



220-240 V | LED |  | IP20 | IK06

TECHNICAL PARAMETERS

Ingress protection:	IP20;
Impact resistance:	IK06;
Nominal power [W]:	50.00;
Luminous flux [lm]*:	3200;
Colour temperature [K]:	4000;
Colour rendering index:	>80;
SDCM:	≤ 3;
Energy efficiency class:	A;
Material of the body:	aluminium;
Diffuser material:	PMMA;
Diffuser type:	OPAL;
Mounting version:	surface; recessed;
Dimensions [mm]:	55/70/1165; 105/85/1165;

*Tolerance +/- 10%

CHARACTERISTICS

Surface or recessed very narrow luminaire including an integrated, energy-saving LED GO! light source. Body made from grey anodized aluminium. The optical system: asymmetric.

APPLICATION

Particularly well suited for indoor use. The fixture is perfect for illumination of boards, paintings and display cases. The fixture is applied mostly in schools, universities, museums and art galleries.

SMART LED EVO ASYMMETRIC

LED GO!

AVAILABLE TYPES

[Click >> index, to see details](#)

SMART LED EVO ASYMMETRIC surface

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions [mm]	Energy efficiency class	Rated power of the luminaire [W]*	Index
50	4000	3200	OPAL	55/70/1165	A	53.50	>> 378256

SMART LED EVO ASYMMETRIC recessed

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Dimensions [mm]	Energy efficiency class	Rated power of the luminaire [W]*	Index
50	4000	3200	OPAL	105/85/1165	A	53.50	>> 378270

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2019-10-11



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



114/2018