SQ 160 LED N





TECHNICAL PARAMETERS

Ingress protection: IP33; IK08; Impact resistance: Nominal power [W]: 17.00; Luminous flux [lm]*: 1700 - 2200

4000; 3000;

Colour temperature [K]: Colour rendering index: >80; Energy efficiency class: A+; A; Material of the body: ABS; Colour of the body: white; Diffuser material: PS;

MAT; PRM; OPAL; Diffuser type: Beam angle [°]: 110; 115; 75; Mounting version: surface;

Working temperature [°C]: from -20 to +35; Dimensions [mm]: 162/162/86; Warranty [years]: 5;

*Tolerance +/- 10%

CHARACTERISTICS

 $\ensuremath{\mathsf{SQ}}$ 160 LED N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.



AVAILABLE TYPES

Click >> index, to see details

SQ 160 LED N 17W

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Beam angle [°]	Energy efficiency class	Index
17	3000	1700	MAT	110	Α	<u>>> 571084</u>
17	4000	1800	MAT	110	A+	<u>>> 570933</u>
17	3000	2100	PRM	115	A+	<u>>> 571138</u>
17	4000	2200	PRM	115	A+	<u>>> 570988</u>
17	3000	2050	OPAL	75	A+	<u>>> 571183</u>
17	4000	2050	OPAL	75	A+	<u>>> 571039</u>

^{*}Tolerance +/- 10%

Lena Lighting S.A. ul. Kórnicka 52 63-000 Środa Wielkopolska









