

BARIS LED KINKIET

LED

LED |  | IP44

TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	16.00; 15.00;
Luminous flux [lm]*:	1400; 1300; 1100; 1700; 1600
Colour temperature [K]:	4000; 3000;
Ingress protection:	IP44;
Energy efficiency class:	A; A+;
Material of the body:	aluminium;
Colour of the body:	grey; white; black;
Diffuser material:	PS;
Diffuser type:	OPAL; PRM;
Mounting version:	surface, wall mounted; Kinkiet;
Dimensions [mm]:	53/71/579;

*Tolerance +/- 10%

CHARACTERISTICS

A luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover.

APPLICATION

The unique design predisposes these luminaires to illuminate: offices, conference rooms and other representative spaces, in offices, passageways, sanitary rooms and bathrooms (wall lamps), in public utility buildings.

BARIS LED KINKIET

LED
AVAILABLE TYPES
[Click >> index, to see details](#)
BARIS LED KINKIET 16W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Colour of the body	DIMM DALI	Dimensions [mm]	Index
16	3000	1300	OPAL	A	grey	yes	53/71/579	>> 318955
16	3000	1300	OPAL	A	white	yes	53/71/579	>> 318993
16	3000	1300	OPAL	A	black	yes	53/71/579	>> 319037
16	3000	1300	OPAL	A	grey		53/71/579	>> 318931
16	3000	1300	OPAL	A	white		53/71/579	>> 318979
16	3000	1300	OPAL	A	black		53/71/579	>> 319013
16	4000	1400	OPAL	A	grey	yes	53/71/579	>> 318948
16	4000	1400	OPAL	A	white	yes	53/71/579	>> 318986
16	4000	1400	OPAL	A	black	yes	53/71/579	>> 319020
16	4000	1400	OPAL	A	grey		53/71/579	>> 318924
16	4000	1400	OPAL	A	white		53/71/579	>> 318962
16	4000	1400	OPAL	A	black		53/71/579	>> 319006
16	3000	1600	PRM	A+	grey	yes	53/71/579	>> 455445
16	3000	1600	PRM	A+	white	yes	53/71/579	>> 455483
16	3000	1600	PRM	A+	black	yes	53/71/579	>> 455520
16	3000	1600	PRM	A+	grey		53/71/579	>> 455421
16	3000	1600	PRM	A+	white		53/71/579	>> 455469
16	3000	1600	PRM	A+	black		53/71/579	>> 455506
16	4000	1700	PRM	A+	grey	yes	53/71/579	>> 455438
16	4000	1700	PRM	A+	white	yes	53/71/579	>> 455476
16	4000	1700	PRM	A+	black	yes	53/71/579	>> 455513
16	4000	1700	PRM	A+	grey		53/71/579	>> 455414
16	4000	1700	PRM	A+	white		53/71/579	>> 455452
16	4000	1700	PRM	A+	black		53/71/579	>> 455490

BARIS LED KINKIET VD 15W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Colour of the body	DIMM DALI	Dimensions [mm]	Index
15	4000	1100	OPAL	A	grey		53/71/579	>> 319044
15	4000	1100	OPAL	A	white		53/71/579	>> 319068
15	4000	1100	OPAL	A	black		53/71/579	>> 319082
15	4000	1350	PRM	A+	grey		53/71/579	>> 455537
15	4000	1350	PRM	A+	white		53/71/579	>> 455544
15	4000	1350	PRM	A+	black		53/71/579	>> 455551

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-12-07


 Lena Lighting S.A.
 ul. Kórnicka 52
 63-000 Środa Wielkopolska

 tel. +48 61 28 60 300
 e-mail: office@lenalighting.pl
 www.lenalighting.pl


The luminaire complies with the EU RoHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).

