

HULK 2 LED MINI BASIC

LED

LED |  | IP66 | IK09

TECHNICAL PARAMETERS

Ingress protection:	IP66;
Impact resistance:	IK09;
Rated power of the luminaire [W]*:	137.00; 151.00;
Luminous flux [lm]*:	14644; 17793;
Colour temperature [K]:	4000;
Colour rendering index:	>80;
SDCM:	≤ 5;
Electrical protection class:	I;
Energy efficiency class:	A+;
Material of the body:	powder coated aluminium;
Diffuser material:	PC;
Diffuser type:	transparent;
Beam angle [°]:	105;
Mounting version:	surface, suspended;
Dimensions [mm]:	42/320;
Warranty [years]:	5;

*Tolerance +/- 10%

CHARACTERISTICS

HULK 2 LED MINI BASIC is a HIGH-BAY lamp from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, designed from scratch, made of die-cast aluminum and powder coated, uses natural conduction and convection processes, which have a positive effect on the heat management of the lamp. The body shape with an integrated, effective heat sink and high-quality materials ensure maximum heat dissipation from the LED module. LEDs from a reputable manufacturer and new LED modules have an impact on high luminous efficacy: up to 109 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The DOB technology used ensures a very high Power Factor (0.99) and long life. The diffuser made of PC polycarbonate provides universal distribution of 105 degrees. Standard equipped with a 0.3 m long H07RN-F cable terminated with an additional male and female connector, facilitating and improving the assembly. Its design is adapted for suspended mounting, and with the use of additional accessories also surface-mounted (ceiling and wall).

Additional accessories:

- protective net
- holder for surface mounting
- universal holder - adjustable

APPLICATION

The luminaire is designed for suspended mounting (using chains, ropes, etc.) both indoors and outdoors. It works perfectly in factories and production halls as well as large-scale warehouses and logistics centers.

HULK 2 LED MINI BASIC

LED

AVAILABLE TYPES

[Click >> index, to see details](#)

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	Diffuser material	Energy efficiency class	Index
137	4000	14644	105	PC	A+	>> 967610
151	4000	17793	105	PC	A+	>> 967627

*Tolerance +/- 10%

ACCESSORIES

Name	Index
OCULUS LED - universal handle	964886
OCULUS LED - surface mounting handle	964893
OCULUS LED MINI - protective grid	967030



OCULUS LED - universal handle (964886)



OCULUS LED - surface mounting handle (964893)



OCULUS LED MINI - protective grid (967030)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2021-02-09



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



15/2021