# QUEST 2 LED ENDURA HB











### **CHARACTERISTICS**

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.



## **TECHNICAL PARAMETERS**

IP66; Ingress protection: IK09; Impact resistance:

Rated power of the luminaire [W]\*: 108 - 290 Luminous flux [lm]\*: 14700 - 40200

Colour temperature [K]: 4000; Colour rendering index: > 80; SDCM: ≤ 3;

Electrical protection class: I; Energy efficiency class: A+; A++; Material of the body: aluminium;

Diffuser material: glass;

Diffuser type: transparent; Beam angle [°]: 120;

Mounting version: suspended; surface; Dimensions [mm]: 321/424/37; 671/424/37; 415/424/37; 859/424/37;

Warranty [years]: 5;

\*Tolerance +/- 10%



### **APPLICATION**

QUEST 2 LED ENDURA is a fitting designed for lighting surfaces with the ambient temperature up to +60°C (eg. for industrial plants or bakeries). The unfavourable conditions of the environment do not have influence on the fitting's reliability and efficacy. In rooms such as cold stores, the requirements for lighting are far from standard. Only the fittings especially suited for working in such conditions can be used in rooms with cold temperatures. is a fitting designed for lighting surfaces with the temperature down to -35°C.



# QUEST 2 LED ENDURA HB





**AVAILABLE TYPES** 

Click >> index, to see details

#### **QUEST 2 LED ENDURA HB surface**

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Version	Mounting version	Dimensions [mm]	Index
108	4000	14700	120	yes	МхГ	surface	321/424/37	<u>&gt;&gt; 696527</u>
108	4000	14700	120		МхГ	surface	321/424/37	<u>&gt;&gt; 698842</u>
145	4000	20100	120	yes	1xL	surface	415/424/37	<u>&gt;&gt; 696589</u>
145	4000	20100	120		1xL	surface	415/424/37	<u>&gt;&gt; 698903</u>
216	4000	29400	120	yes	2xM	surface	671/424/37	<u>&gt;&gt; 696534</u>
216	4000	29400	120		2xM	surface	671/424/37	<u>&gt;&gt; 698859</u>
290	4000	40200	120	yes	2xL	surface	859/424/37	<u>&gt;&gt; 696596</u>
290	4000	40200	120		2xL	surface	859/424/37	<u>&gt;&gt; 698910</u>

### **QUEST 2 LED ENDURA HB suspended**

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Beam angle [°]	DIMM DALI	Version	Mounting version	Dimensions [mm]	Index
108	4000	14700	120	yes	МхF	suspended	321/424/37	<u>&gt;&gt; 696404</u>
108	4000	14700	120		ТхМ	suspended	321/424/37	<u>&gt;&gt; 698729</u>
145	4000	20100	120	yes	1xL	suspended	415/424/37	<u>&gt;&gt; 696466</u>
145	4000	20100	120		1xL	suspended	415/424/37	<u>&gt;&gt; 698781</u>
216	4000	29400	120	yes	2xM	suspended	671/424/37	<u>&gt;&gt; 696411</u>
216	4000	29400	120		2xM	suspended	671/424/37	<u>&gt;&gt; 698736</u>
290	4000	40200	120	yes	2xL	suspended	859/424/37	<u>&gt;&gt; 696473</u>
290	4000	40200	120		2xL	suspended	859/424/37	<u>&gt;&gt; 698798</u>

### **ACCESSORIES**

Name	Index
QUEST PLUS LED M protective grid RAL9006	559907
QUEST PLUS LED L protective grid RAL9006	559914
QUEST PLUS LED HB M protective grid RAL9006 single suspension	559952
OUEST PLUS LED HB L protective arid RAL9006 sinale suspension	559945



QUEST PLUS LED M protective grid RAL9006 (559907)



QUEST PLUS LED L protective grid RAL9006 (559914)



QUEST PLUS LED HB M protective grid RAL9006 single suspension (559952)



QUEST PLUS LED HB L protective grid RAL9006 single suspension (559945)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.





RoHS





This product is a subject to electric and electronic waste equipment regulations (WEEE).

